



THE FENDER BCS GROUP OF COMPANIES

www.fenderbcs.co.uk

SUPA-FIX P

MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME SUPA-FIX P
APPLICATION Component of two part polyester resin based product

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BENZOYL PEROXIDE	202-327-6	94-36-0	0.2-0.5%	E;R2 R43 Xi;R36

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Inert filler containing dibenzoyl peroxide The product contains calcium carbonate.

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Irrigate the eyes with water or proprietary eye-wash for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Product formulation renders the product a minimal fire risk even in a general fire situation Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES Avoid breathing fire vapours.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Avoid inhalation of dust.

SPILL CLEAN UP METHODS

Avoid dust formation. Preferably remove spillage with a vacuum cleaner. If not possible dampen with water and collect spillage with a shovel, broom or the like.

Our expertise is fitting all the pieces together

Fender Steel

Head Office
20 Midland Road
Scunthorpe
North Lincolnshire
DN16 1DQ
Tel: 01724 840609
Fax: 01724 281902

BCS Products

Caenby Corner
Industrial Estate
Hemswell Cliff
Nr. Gainsborough
Lincolnshire DN21 5TU
Tel: 01427 668187
Fax: 01427 668012

Fender Steel

Unit 16A
Enterprise Park,
Bergon Way
Sutton Fields Ind. Est.,
Hull HU7 0YG
Tel: 01482 820620
Fax: 01482 820621

Fender Steel

Unit A5
Astra Park
Parkside Lane
Leeds LS11 5SZ
Tel: 0113 270 4555
Fax: 0113 270 4666

Fender Steel

5 Crofton Court
Portrack Lane
Stockton-on-Tees
Cleveland TS18 2QR
Tel: 01642 603123
Fax: 01642 674892

Fender Steel

5a Freezemoor Road
Houghton le Spring
Sunderland
Tyne & Wear DH4 7BH
Tel: 0191 512 6749
Fax: 0191 584 6547

USAGE PRECAUTIONS

Avoid handling which leads to dust formation. Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep separate from food, feedstuffs, fertilisers and other sensitive material. Do not store near heat sources or expose to high temperatures.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m ³	ST - ppm	ST - mg/m ³
BENZOYL PEROXIDE	OES		5 mg/m ³		

INGREDIENT COMMENTS

The product may contain a low level of respirable crystalline silica (MEL 0.3 mg/m³; 8 hours TWA). General nuisance dust levels should be controlled to OES (8hr TWA):- 10mg/m³ total inhalable dust 4mg/m³ respirable dust.

ENGINEERING MEASURES Provide sufficient ventilation for operations causing dust formation.

RESPIRATORY EQUIPMENT Wear suitable respiratory protection.

HAND PROTECTION For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent repeated or prolonged skin contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Coarse powder

ODOUR Slight odour

BULK DENSITY Variable -depends on packing effects

VOLATILE BY VOL. (%) N/A

pH-VALUE, CONC. SOLUTION N/A **VISCOSITY** N/A

FLASH POINT (°C) N/A

10 STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID Avoid contact with acids and alkalis. Avoid contact with strong reducing agents.

11 TOXICOLOGICAL INFORMATION

INHALATION

Dust in high concentrations may irritate the respiratory system. The product may contain a small percentage of respirable crystalline silica. Prolonged exposure to dust may result in long term irreversible effects

INGESTION

Unlikely to occur in normal use. No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Prolonged or repeated exposure may cause some irritation of the skin.

EYE CONTACT May cause temporary eye irritation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Powder to be collected, sealed tightly in bags and disposed on approved landfills.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

ADR CLASS Not classified for transportation. **MARINE POLLUTANT** No.

15 REGULATORY INFORMATION

RISK PHRASES NC Not classified.

SAFETY PHRASES P14 Contains BENZOYL PEROXIDE. May produce an allergic reaction.

16 OTHER INFORMATION

GENERAL INFORMATION

Don Construction Products Ltd. Technical Datasheet.

INFORMATION SOURCES

Health and Safety Executive Guidance Note EH40 (amended annually). Occupational Exposure Limits. Respirable crystalline silica is subject to a Chemicals Hazard Alert Notice (CHAN) Number 35. Text can be found at <http://www.hse.gov.uk/pubns/chan35.htm>.

REVISION DATE 1/11/04

REV. NO./REPL. SDS GENERATED 2

RISK PHRASES IN FULL

R2 Risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.