



THE FENDER BCS GROUP OF COMPANIES

www.fenderbcs.co.uk

# Supa-Plug

## Wall Tie Sealing Compound

**1. SUPA-PLUG**

IDENTIFICATION OF COMPOUND SUPA-PLUG:

Wall tie sealing compound.

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Contains:

Chemical Name	CAS No	Concentration(%w/w)
Portland Cement	65997-15-1	>25%
<b>Hazard Symbol</b>	Xi	
<b>Risk Phrases</b>		
R3 6/3 8:	Irritating to eyes and skin.	
R41:	Risk of serious damage to eyes	

**3. HAZARDS IDENTIFICATION**

Irritating to eyes and skin. Risk of serious damage to the eyes. Product forms a strong alkaline solution on contact with water or moisture. Repeated or prolonged contact of the skin with the product or its solutions may cause irritant or allergic contact dermatitis. Product may cause serious burns and ulceration. May be toxic to aquatic life in some circumstances.

**4. FIRST AID MEASURES**

**Eyes:** Flush eyes with copious amounts of water for at least 15 minutes. Seek medical advice.

**Skin:** Remove contaminated clothing. Wash skin with soap and water. Seek medical advice if any irritation persists.

**Inhalation:** If irritation occurs, move to fresh air. If nose or airways become inflamed seek medical advice.

**Ingestion: Do not induce vomiting.** Wash out mouth with water, give 200-300 ml of water to drink and seek medical attention if victim feels unwell.

**5. FIRE FIGHTING MEASURES**

This product is not flammable and will not facilitate combustion with other materials.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Wear full protective clothing and goggles. The use of breathing apparatus in confined spaces is recommended.

**Environmental Precautions:** Do not allow product to enter drains or water courses. Advise local authorities if this is not possible.

**Clean Up Methods:** Recover the spillage in a dry state, minimising the generation of airborne dust.

**7. HANDLING AND STORAGE**

**Handling:** Avoid contact with eyes/skin. Do not breath dust. Provide adequate ventilation, including local extraction if necessary. Use appropriate breathing apparatus if this is not possible.

**Storage:** Keep container sealed when not in use. Avoid contact with moisture.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Portland Cement****Total inhalable dust (LTEL):**10mg/m<sup>3</sup> 8hr TWA**Respirable dust (LTEL):**4mg/m<sup>3</sup> 8hr TWA

Good working practice suggests that full protective clothing and goggles should be worn when handling this product. Dust levels should be controlled by engineering methods where practicable. Suitable respiratory protection should be worn if dust exposure is likely to be above the OEL.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance:** Grey granular powder.**10. STABILITY AND REACTIVITY**

Will hydrate in contact with water or water vapour.

**11. TOXICOLOGICAL INFORMATION**

**Inhalation:** Powder may cause inflammation of the mucous membranes.

**Skin Contact:** Powder or any powder/water mixtures may cause irritant contact dermatitis, allergic (chromium) dermatitis and/or burns.

**Eye Contact:** Powder is a severe eye irritant. Mild exposure can cause soreness. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye.

**Ingestion:** Unlikely to cause any significant reaction. Large doses may result in gastro intestinal irritation.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity:** The addition of the powder to water will raise the pH and therefore may be toxic to aquatic life in some circumstances.

**13. DISPOSAL CONSIDERATIONS**

Dispose of product and contaminated containers to a place authorised to accept builders' waste.

**14. TRANSPORT INFORMATION**

Not classed as hazardous for transport.

**15. REGULATORY INFORMATION****Classification:** Irritant**Hazard symbol:** Xi**Risk Phrases:**

R36/38 Irritating to eyes and skin.

R41 Risk of serious damage to eyes.

**Safety Phrases:**

S2 Keep out of reach of children.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of soap and water.

S36/39 Wear suitable protective clothing and eye/face protection.

**16. OTHER INFORMATION**

Every effort has been made to ensure that the information contained in this safety data sheet is reliable but we cannot accept any liability for any loss, injury or damage which may result from use of the product. This information does not constitute assessment of risk as required by health and safety legislation. Data given in this safety data sheet are solely for guidance in safe handling and use of the product by customers; they do not form part of any specification.

*Our expertise is fitting all the pieces together*

**Fender Steel**

Head Office  
20 Midland Road  
Scunthorpe  
North Lincolnshire  
DN16 1DQ  
Tel: 01724 840609  
Fax: 01724 281902

**BCS Products**

Caenby Corner  
Industrial Estate  
Hemswell Cliff  
Nr. Gainsborough  
Lincolnshire DN21 5TU  
Tel: 01427 668187  
Fax: 01427 668012

**Fender Steel**

Unit 16A  
Enterprise Park,  
Bergon Way  
Sutton Fields Ind. Est.,  
Hull HU7 0YG  
Tel: 01482 820620  
Fax: 01482 820621

**Fender Steel**

Unit A5  
Astra Park  
Parkside Lane  
Leeds LS11 5SZ  
Tel: 0113 270 4555  
Fax: 0113 270 4666

**Fender Steel**

5 Crofton Court  
Portrack Lane  
Stockton-on-Tees  
Cleveland TS18 2QR  
Tel: 01642 603123  
Fax: 01642 674892

**Fender Steel**

5a Freezemoor Road  
Houghton le Spring  
Sunderland  
Tyne & Wear DH4 7BH  
Tel: 0191 512 6749  
Fax: 0191 584 6547