



THE FENDER BCS GROUP OF COMPANIES

www.fenderbcs.co.uk

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product **Supa-Cleanse** **Single Pack**
Company Name Resin Building Products Ltd
 Resbuild House
 Unit 2, Durham Lane
 Armthorpe
 Doncaster, UK
 DN3 3FE
 Tel: +44 (0) 1302 300822
 Fax: +44 (0) 1302 300833
 www.resbuild.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	Name	EC No	CAS -No	Content	Symbol	R Phrase
	1-Methoxy-2-Propanol	203-539-1	107-98-2	>99.5%	F	R10

3. HAZARDS IDENTIFICATION

Main Hazards Flammable.

4. FIRST AID MEASURES

Skin contact Wipe with absorbent paper disposable towels. Wash with plenty of soap and water. In case of dermatitis or if irritation persists, get medical attention. Immediately flush eyes with running water for at least 15 minutes without interruption. Seek medical advice.

Eye contact Immediately rinse the mouth with water. If swallowing has occurred drink plenty of water. Seek medical attention promptly.

Ingestion Move affected person to fresh air. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Inhalation

5. FIRE-FIGHTING MEASURES

Extinguishing media Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc

Exposure hazards Drums may explode.

Protection of fire-fighters Wear full protective clothing and self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid skin, eye and clothing contact. Wear suitable protective clothing. Provide sufficient ventilation during use.

Environmental precautions Prevent from entering sewer system, surface water or soil.

Clean-up procedures Soak up with absorbent material e.g. dry sand, vermiculite, and dispose of as instructed (see section 13).

Our expertise is fitting all the pieces together

Fender Steel

Head Office
 20 Midland Road
 Scunthorpe
 North Lincolnshire
 DN16 1DQ
 Tel: 01724 840609
 Fax: 01724 281902

BCS Products

Caenby Corner
 Industrial Estate
 Hemswell Cliff
 Nr. Gainsborough
 Lincolnshire DN21 5TU
 Tel: 01427 668187
 Fax: 01427 668012

Fender Steel

Unit 16A
 Enterprise Park,
 Bergon Way
 Sutton Fields Ind. Est.,
 Hull HU7 0YG
 Tel: 01482 820620
 Fax: 01482 820621

Fender Steel

Unit A5
 Astra Park
 Parkside Lane
 Leeds LS11 5SZ
 Tel: 0113 270 4555
 Fax: 0113 270 4666

Fender Steel

5 Crofton Court
 Portrack Lane
 Stockton-on-Tees
 Cleveland TS18 2QR
 Tel: 01642 603123
 Fax: 01642 674892

Fender Steel

5a Freezemoor Road
 Houghton le Spring
 Sunderland
 Tyne & Wear DH4 7BH
 Tel: 0191 512 6749
 Fax: 0191 584 6547

7. HANDLING AND STORAGE

- Handling requirements** Use in well ventilated areas. Keep containers tightly closed when not in use. Avoid contact with skin, eyes and clothing. Keep away from sources of ignition. No smoking. Do not eat drink or smoke at the work place.
- Storage conditions** Keep away from food and drink. Store in original container securely closed in a cool dry place. Keep away from sources of ignition. Do not leave drums open. Earth storage containers during transport. Must only be kept in original packaging.
- Suitable packaging**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering measures** Ensure there is sufficient ventilation of the area.
- Respiratory Protection** Chemical Cartridge
- Hand protection** Protective gloves of PVC or rubber.
- Eye protection** Wear suitable goggles or face protection..
- Skin protection** Standard issue work clothes. Safety boots/shoes; chemical resistant.

Exposure Control Limits	Ingredient	LT EXP.(8hrs)	ST EXP (15 mins)
	1-Methoxy-2-propanol	100 ppm	150 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

- State** Liquid.
- Colour** Colourless
- Odour** Mild (or faint). Alcohol
- Solubility in water** Miscible with water
- Density** 0.92
- Flash point °C** 32°C

10. STABILITY AND REACTIVITY

- Stability** >200°C
- Conditions to avoid** Do not leave containers open when not in use.
- Materials to avoid** Heat, sparks, and flames. Strong oxidizing agents
- Haz. Decompositon Products** ..

11. TOXICOLOGICAL INFORMATION

- Ingestion** LD50 Acute oral toxicity in rats : 5000mg/kg.
- Eye Contact** Eye irritation tested in rabbits : Irritant
- Skin Contact** Skin irritation tested in rabbits : Irritant
- Inhalation** Vapour concentrations above the recommended exposure levels are irritating to eyes and respiratory tract and may cause headaches and dizziness

12. ECOLOGICAL INFORMATION

- Mobility** Readily absorbed into soil. Prevent contamination of soil, drains or surface water.
- Ecotoxicity** This product is expected to be toxic to aquatic organisms.
- Degradability** The product is biodegradable

13. DISPOSABLE CONSIDERATIONS

Incineration or landfill in accordance with local regulations. Contaminated packaging materials should be disposed of identically to the product itself. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

14. TRANSPORT INFORMATION

ADR/RID

UN no	3092	ADR Class	3 : Flammable Liquid
Packing Group	III	Classification code	2Y
Proper Shipping Name	1-Methoxy-2-Propanol	Hazard ID no	31c

IMDG/IMO

UN no	3092	Class	3.3
Packing Group	III	EmS	F-E, S-D
Marine Pollutant	No	Labelling	3

IATA/ICAO

UN no	3092	Class	3
Packing Group	III	Packing Instruction	307
Labelling	3		

15. REGULATORY INFORMATION

Hazard Symbol	F; Flammable
Risk Phrases	R10, Flammable
Safety Phrases	S24, Avoid contact with skin

16. OTHER INFORMATION**Other information****Legal disclaimer**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Resin Building Products Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.