



THE FENDER BCS GROUP OF COMPANIES

www.fenderbcs.co.uk

SUPA-CRETE ExCeL MATERIAL SAFETY DATA SHEET

1. Identification of the substance/preparation and of the company

1.1 Identification of the product

Supa-Crete ExCeL

1.2 Use of the product

Concrete Repair

1.3 Company identification

Fender Steel Ltd

20 Midland Road

Scunthorpe

N. Lincs

Tel: 01724 840609

Fax: 01724 281902

2. Composition/information on ingredients

Blend of Portland Cement, silica aggregates and additives.

3. Hazard identification

Supa-Crete ExCeL should be treated in the same way as Portland Cement which when mixed with water might cause alkali burns. Contains Chromium (VI). Might produce an allergic reaction.

4. First Aid Measures

Skin Contact: Wash with water followed by water and soap.

Eye Contact: Rinse immediately with water or an eye wash solution for at least 15 minutes.

Inhalation: Treat symptomatically.

Ingestion: Give water or milk to drink, do not induce vomiting. Treat symptomatically.

5. Fire fighting measures

Supa-Crete ExCeL is not flammable and will not facilitate combustion with other materials.

6. Accidental release measures

Personal precautions

See Section 8.

Methods for cleaning

Protect against dust. Sweep up and shovel into suitable and closable container, for disposal according to local regulations. Wash the area clean with water.

Our expertise is fitting all the pieces together

Fender Steel

☐ Head Office
20 Midland Road
Scunthorpe
North Lincolnshire
DN16 1DQ
Tel: 01724 840609
Fax: 01724 281902

BCS Products

☐ Caenby Corner
Industrial Estate
Hemswell Cliff
Nr. Gainsborough
Lincolnshire DN21 5TU
Tel: 01427 668187
Fax: 01427 668012

Fender Steel

☐ Unit 16A
Enterprise Park,
Bergon Way
Sutton Fields Ind. Est.,
Hull HU7 0YG
Tel: 01482 820620
Fax: 01482 820621

Fender Steel

☐ Unit A5
Astra Park
Parkside Lane
Leeds LS11 5SZ
Tel: 0113 270 4555
Fax: 0113 270 4666

Fender Steel

☐ 5 Crofton Court
Portrack Lane
Stockton-on-Tees
Cleveland TS18 2QR
Tel: 01642 603123
Fax: 01642 674892

Fender Steel

☐ 5a Freezemoor Road
Houghton le Spring
Sunderland
Tyne & Wear DH4 7BH
Tel: 0191 512 6749
Fax: 0191 584 6547

7. Handling & storage

Handling

Due regard should be paid to the risks outlined in the Manual Handling Operations Regulations 1992. Some bags might have small amount of material on the outer surface. Appropriate personal protective clothing (see section 8) should therefore be used while handling.

Storage

Bags should be stacked in a safe and stable manner.

8. Exposure controls/Personal protection

Occupational Exposure limits: Based on 8 hour TWA Total inhalable dust - 10mg/m³
Respirable dust - 4mg/m³

Refer to H&S - EH40 for further guidance.

Personal Protective Equipment: Wear overalls, approved dust masks, eye protection and safety footwear.

9. Physical and chemical properties

Appearance:	Coarse grey powder
Odour:	None
pH:	12 to 14
Boiling point:	Not applicable
Melting point:	Not applicable
Flash point:	Not applicable
Flammability:	None
Autoflammability:	Not applicable
Explosive properties:	Not applicable
Oxidising properties:	Not applicable
Vapour pressure:	Not applicable
Relative density:	Not applicable
Solubility:	Insoluble in water

10. Stability & reactivity

Stability:	Hazardous reactions not known
Conditions to avoid:	None
Materials to avoid:	None
Hazardous decomposition products:	None

11. Toxicological information

Short term effects:	Portland cement can cause chemical burning and ulceration of eyes: contact with skin can cause irritant and allergic dermatitis especially mixtures with water. Ingestion of large doses might result in irritation of the gastro intestinal tract. Cement powder might cause inflammation of mucous membranes.
Long term effects:	Prolonged and repeated exposure might cause irritant contact dermatitis and/or allergic (chromium) dermatitis. Allergic dermatitis more commonly arises through contact with cement/water mixtures than dry cement. High repeated exposures in excess of the OES have been linked with rhinitis and coughing.

12. Ecological information

Mobility:	Dust might be spread by the wind.
Degradability:	Immiscible with water and will react with water to produce inert and non biodegradable solids.
Bioaccumulation:	No data.
Aquatic Toxicity:	LC50 aquatic toxicity not known. The addition of cement to water will however cause pH to rise and might therefore be toxic to aquatic life in some circumstances.

13. Disposal considerations

Disposal of material should be in accordance with local regulations. Keep out of reach of children.

14. Transport information

Classification for conveyance: Not required.

15. Regulatory information

Labelling according to CHIP 1996: Classification - not classified
Hazard symbol - Irritant

Risk Phrases: R38 Irritating to skin
R41 Risk of serious damage to eyes
R43 May cause sensitisation by skin contact

15. Regulatory information (cont'd)

Safety Phrases: S22 Do not breathe dust
S24 Avoid contact with skin
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37/39 Wear suitable gloves and eye/face protection.

EINECS Number: Not applicable

16. Other Information

CONIAC Health Hazard Information Sheet No. 26 (Cement)
Health & Safety at Work etc Act 1974
Control of Substances Hazardous to Health Regulations 1998
Portland Cement Dust: criteria document for an occupational exposure limit. June 1994 (ISBN 0-7176-0763-1)
HSE Guidance Note EH26 (Occupational Skin Diseases: Health & Safety Precautions), HMSO 1981
HSE Leaflet MS(B)9: Save your skin, advice to employers (1987)
HSE Guidance Note EH40 (Occupational Exposure Limits)
Any authorised manual on First Aid by St. John's/St Andrew's/Red Cross
Manual Handling Operations Regulations 1992