

**Description**

Supa-Cleanse is an equipment cleaner suitable for the removal of uncured Epoxy, Polyester and Polyurethane resins.

It has a low evaporation rate, mild odour and low toxicity, making it much more user friendly than other commonly used solvents.

Supa-Cleanse is also largely biodegradable and photochemically non-reactive, and therefore more acceptable from an environmental point of view.

Typical Uses

Equipment cleaning.
Uncured resin removal.
Paint and Graffiti removal.

Advantages

- Low Hazard
- Low evaporation rate
- Excellent solvency powers
- 80% Biodegradable

Typical Properties

Appearance: clear, colourless liquid

Odour: mild, sweet

Flash Point: 31°C

Vapour Pressure: 10mm Hg @ 20°C

Specific Gravity: 0.921 @ 20°C

Solubility in water: Soluble

Packaging

Supa-Cleanse is supplied in 5ltr packs

Health and Safety

Do not breathe vapour/spray.
Avoid contact with skin and eyes.
Provide adequate ventilation.

Refer to Material Safety Date Sheet for further information.

Supa-Cleanse shall be applied strictly in accordance with the manufacturer's instructions.

For specific advice regarding any aspect of this product please consult our Technical section.

Storage and Shelf Life

Store in dry conditions, out of direct sunlight, at temperatures between 10°C and 25°C.

Supa-Cleanse has a minimum shelf life of 12 months when stored in original, unopened containers in accordance with manufacturer's instructions.

The information provided in this Product Data Sheet is intended for general guidance only and is given in good faith based on Fender BCS Group current knowledge and experience. No warranty in respect of fitness for a purpose, or any other liability whatsoever can be inferred from the information contained within this data sheet. Users should determine the suitability of the materials for their particular application and should always refer to the most recent issue of the Product Data Sheet for the product concerned. All materials are supplied in accordance with our standard terms and conditions of sale (available upon request).

Our expertise is fitting all the pieces together

Fender Steel

Head Office
20 Midland Road
Scunthorpe
North Lincolnshire
DN16 1DQ
Tel: 01724 840609
Fax: 01724 281902

BCS Products

Caenby Corner
Industrial Estate
Hemswell Cliff
Nr. Gainsborough
Lincolnshire DN21 5TU
Tel: 01427 668187
Fax: 01427 668012

Fender Steel

Unit 16A
Enterprise Park,
Bergon Way
Sutton Fields Ind. Est.,
Hull HU7 0YG
Tel: 01482 820620
Fax: 01482 820621

Fender Steel

Unit A5
Astra Park
Parkside Lane
Leeds LS11 5SZ
Tel: 0113 270 4555
Fax: 0113 270 4666

Fender Steel

5 Crofton Court
Portrack Lane
Stockton-on-Tees
Cleveland TS18 2QR
Tel: 01642 603123
Fax: 01642 674892

Fender Steel

5a Freezemoor Road
Houghton le Spring
Sunderland
Tyne & Wear DH4 7BH
Tel: 0191 512 6749
Fax: 0191 584 6547